



Type ZL xx-AB strain relief



EMC solutions

PRODUCT INFORMATION

In conjunction with the ZL strain relief rail, the ZL-AB discharge plate is suitable for discharging interferences which may occur on cable sheaths. ZL strain relief not included in delivery. Please order separately.

SPECIFICATIONS

Stainless steel 1.4301

Type	Order No.	Installation height mm	A mm	B mm	c mm	e mm	MOQ qty.
ZL 140-AB/EMV ¹⁾	87701046	12.00	142.50	25.00	121.00	6.50	1

¹⁾ The corresponding ZL strain relief plate is required for the discharge plate.

MATERIAL PROPERTIES

Stainless steel 1.4301

FIRE PROPERTIES

CONFORMITY

RoHS (EC Directive 2011/65/EU)

APPROVALS AND OPERATING PERMITS

GL approval

All details given in our sales brochures and catalogues, as well as the information available online, are based on our current knowledge of the products described.

The electronic data and files made available by Murrplastik, particularly CAD files are based on our current knowledge of the product described.

A legally binding assurance of certain properties or the suitability for a certain purpose can not be determined from this information.

All information with respect to the chemical and physical properties of Murrplastik products, as well as application advice given verbally, in writing or by tests, is given to the best of our knowledge.

They do not release the buyer from the obligation to carry out his own tests and trials in order to determine the concrete suitability of the products for the intended purpose.

Murrplastik accepts no responsibility for the available information being up-to-date, correct or complete. Neither do we accept responsibility for the quality of this information.

Murrplastik accepts no liability for damage caused as a result of using our products.

Murrplastik reserves the right to make technical changes and improvements through constant further development of products and services.

Our General Terms and Conditions apply.